

# Hybrid Circuit

---

- Power Profiling Control Circuit
- Commercial Components, Battery
- High Density Circuit
- 8 Puff Delivery (20-30 Watt-Seconds)
- Single Battery System
- 10 x 25 mm Circuit Size Goal  
(Custom Circuit, Battery  
Alternatives)



2020131488

Dec. version

smaller circuit  
puff on demand logic  
single battery operation  
8 puff article  
~~20-27~~ joules (watt-seconds)  
improved puff sensor (4 x sensitivity, 1/5 power consumption)  
article logic always powered  
6 integrated circuits

Jan. version

272- ~~20x~~ thinner than Dec. version

~~25-35~~ joules (watt-seconds)

56 grams vs 80 grams

powered only when flavor insert (load) plugged in

5 integrated circuits vs 6

Siliconix dual FETs (field effect transistors) 2:1 size reduction is

Lower FET "on-resistance" (trapped voltage gate drive)

optimized current paths (lower circuit resistance)

IC

2020131489

"JTX"

## Electronic Module

---

- Microcomputer Based
- Control Functionality Is Programmable
- Complex Circuit
- Two Separate Battery Systems
- 160 Puffs (10 Watt-Seconds)



2020131490

## 1/2 Sized Circuit

- Puff-On-Demand Control Circuit
- Commercial Components and Battery
- High Density Printed Circuit
- Novel Packaging
- New Puff Sensor
  - 1/5 Power of Motorola Sensor
  - 4X Sensitivity
  - Reduced Circuit Complexity
- 8 Puff Delivery (20-30 Watt-Seconds)
- Single Battery for Logic and Heaters



2020131491